

# CSE 304

# Compiler Design

Implementation of a Compiler

---

YOUNGMIN KWON / TONY MIONE

# Overview

---

We will learn how various parts of a program are translated into assembly codes.

# Definition: Program/Function/Procedure

---

```
program
: program_def { Translate($1); }
;
program_def
: PROGRAM ID ';' opt_definition_list BEGIN_ opt_stmt_list END { $$ = CreateProgramDef... }
;
function_def
: FUNCTION ID '(' opt_formal_param_list ')' ':' basic_type ';' opt_variable_def_list /*for NESTED_FUNC, use opt_definition_list*/ BEGIN_ opt_stmt_list END { $$ = CreateFunctionDef... }
;
procedure_def
: PROCEDURE ID '(' opt_formal_param_list ')' ';' opt_variable_def_list /*for NESTED_FUNC, use opt_definition_list*/ BEGIN_ opt_stmt_list END { $$ = CreateFunctionDef... }
;
```

# Definitions: Variables

---

```
variable_def          type
  : VAR variable_type_pair ';'      : array_type
;                      ;
variable_type_pair    array_type
  : variable_list ':' type        : ARRAY '[' NUM ']' OF
;                      ;           array_type
variable_list         | ptr_type
  : variable_list ',' ID         | ptr_type
| ID                 ;           ;
;                     basic_type
;                     : INTEGER
;                     | REAL
;                     | '(' type ')'
;
```

# Definitions: Factor

---

```
factor
: '(' expr ')'
| NUM
| ID
| ID '(' opt_actual_param_list ')' { $$ = CreateFunctionCall... }
| ID '[' actual_param_list ']' { $$ = CreateArrayIndex... }
;
opt_actual_param_list
: actual_param_list
|
;
actual_param_list
: actual_param_list ',' expr { $$ = AddToActualParamList... }
| expr { $$ = AddToActualParamList... }
;
```

Quiz: modify the syntax to use C-style array indexing. (e.g. a[1][2])

# Symbol Table

---

```
struct SymTableEntry
{
    char *id;           //name of the id
    struct Type* type; //type of the id
    bool isGlobal;     //whether id is a global var
    int offset;         //local variable offset from bp
    int size;           //size of the local variable
    int label;          //label for function
    SymTableEntry *next;

    SymTableEntry();
    SymTableEntry(char* id, bool isGlobal);
    SymTableEntry* SetId(char* id);
    SymTableEntry* SetIsGlobal(bool isGlobal);
    SymTableEntry* SetType(Type* type);
    SymTableEntry* SetOffset(int offset);
    SymTableEntry* SetLabel(int label);
    SymTableEntry* SetNext(SymTableEntry* next);
    SymTableEntry* Find(char* id);
};
```

# Symbol Table

---

```
struct SymTable
{
    SymTableEntry head;      //link to the first entry
    int varSize;             //size of variables to allocate
    SymTable* nextScope;   //link to the next scope
    SymTable* next;          //link all tables created
    static SymTable* latestTable;

    SymTable();
    SymTableEntry* Find(char* id, int* linkCount);
    SymTableEntry* Insert(char* id);

    static SymTable* PushNewTable(SymTable* top);
    static SymTable* PopTable(SymTable* top);
};
```

# SyntaxNode (Base Type)

---

```
struct SyntaxNode
{
    virtual int Tag();
    // Update Symbol Table
    virtual void Pretranslate(SymTable* symTable);

    // Translate this node
    virtual void Translate(SymTable* symTable);

    // For LHS, to pass function, array, struct...
    virtual void TranslateAsLValue(
        SymTable* symTable);
};
```

# Translation of Number

---

```
SyntaxNum::SyntaxNum(double value)
    : value(value)
{
    FUNCTION_TRACE;
}

void SyntaxNum::Translate(SymTable* symTable)
{
    FUNCTION_TRACE;

    // Saving the result at rax
    // Round to the nearest number (handling int only)
    printf("    mov      rax, %d\n", (int)(value + .5));
}
```

# Translation of Id

---

```
void SyntaxId::TranslateAsLValue(SymTable* symTable)
{
    int linkCount = 0;
    SymTableEntry *entry = symTable->Find(id, &linkCount);
    if(entry == NULL)
        errQuit("Unknown variable %s.\n", id);

    if(entry->type->typeTag == TypeFunction)
    {
        printf("    mov      rax, label_%03d ; %s\n",
               entry->label, entry->id);
    }
    else if(entry->isGlobal)
    {
        printf("    mov      rax, global_vars + %d ; %s\n",
               entry->offset, entry->id);
    }
    else /*parameters and local variables*/
    {
        printf("    lea      rax, [rbp + %d] ; %s\n",
               entry->offset, entry->id);
    }
}
```

# Translation of Id

---

```
void SyntaxId::Translate(SymTable* symTable)
{
    TranslateAsLValue(symTable);

    int linkCount = 0;
    SymTableEntry *entry = symTable->Find(id, &linkCount);

    // Treat array and function names as a reference
    // Array index and Function call are handled separately.
    bool toReference = entry->type->typeTag == TypeArray ||
                      entry->type->typeTag == TypeFunction ||
                      entry->type->typeTag == TypeProduct;

    if(!toReference)
    {
        printf("      mov      rax, [rax]\n");
    }
}
```

# Translation of Expr

---

```
// Saving the result at rax
void SyntaxExpr::Translate(SymTable* symTable)
{
...
    if(op == OpAddressOf)
        lexpr->TranslateAsLValue(symTable);
    else
        lexpr->Translate(symTable);

    // For binary operators, rax = operand 1, rbx = operand 2
    if(rexpr)
    {
        // push/pop rax is less than efficient, but we don't
        // know what registers will be used in rexpr->Translate.
        printf("    push    rax\n");
        rexpr->Translate(symTable);
        printf("    mov     rbx, rax\n");
        printf("    pop     rax\n");
    }
...
}
```

# Translation of Expr

---

```
...
switch(op)
{
    case '+': printf("add    rax, rbx\n"); break;
    case '-': printf("sub    rax, rbx\n"); break;
    case '*': printf("imul   rbx\n"); break;
    case '/': printf("xor    rdx, rdx\n");
                printf("idiv   rbx\n"); break;
    case OpNeg: printf("neg    rax\n"); break;
    case OpAND: printf("and    rax, rbx\n"); break;
    case OpOR:  printf("or     rax, rbx\n"); break;
    case OpNOT: printf("not    rax\n"); break;
    case OpValueOf: printf("mov    rax, [rax]\n"); break;
...
}
```

Quiz: Write a code for OpEQ

# Translation of Expr

---

```
const char* jmpFmt = NULL;
switch(op)
{
...
case OpEQ:      jmpFmt="    je      label_%03d\n";      break;
case OpNE:      jmpFmt="    jne     label_%03d\n";      break;
case OpGE:      jmpFmt="    jge     label_%03d\n";      break;
case OpGT:      jmpFmt="    jg      label_%03d\n";      break;
case OpLE:      jmpFmt="    jle     label_%03d\n";      break;
case OpLT:      jmpFmt="    jl      label_%03d\n";      break;
}

if(jmpFmt != NULL)
{
    int label = newLabel();
    printf("    mov      rcx, 1\n");
    printf("    cmp      rax, rbx\n");
    printf(jmpFmt, label);
    printf("    xor      rcx, rcx\n");
    printf("label_%03d:\n", label);
    printf("    mov      rax, rcx\n");
}
```

# Assignment Statement

---

```
void SyntaxAssignStmt::Translate(SymTable* symTable)
{
...
else
{
    SyntaxExpr* lvalue = (SyntaxExpr*)expr;
    lvalue->TranslateAsLValue(symTable);

    printf("    push    rax\n");
    rexpr->Translate(symTable);
    printf("    pop     rbx\n");

    // copy rax to the address rbx is pointing to
    printf("    mov     [rbx], rax\n");
}
...
}
```

# Assignment Statement

---

```
void SyntaxAssignStmt::Translate(SymTable* symTable)
{
    // check if this is for the return value. e.g. foo := 1
    bool isReturnValue = false;
    if(expr->Tag() == TagSyntaxId)
    {
        SyntaxId* idExpr = (SyntaxId*)expr;
        int linkCount = 0;
        SymTableEntry* entry = symTable->Find(idExpr->id, &linkCount);
        if(entry && entry->type &&
           entry->type->typeTag == TypeFunction)
            isReturnValue = true; // TODO: check the function name
    }

    if(isReturnValue)
    {
        expr->Translate(symTable);
        printf("    mov    r15, rax\n"); // r15 keeps the return value
    }
    ...
}
```

# Conditional Statement

---

```
void SyntaxCondStmt::Translate(SymTable* symTable)
{
    if(elseStmt)
        ...
    else
    {
        int labelExit = newLabel();

        PRNCMT("      ;; if then\n");
        test->Translate(symTable);
        printf("      cmp      rax, 0\n");
        printf("      jz       label_%03d\n", labelExit);

        PRNCMT("      ;; then\n");
        thenStmt->Translate(symTable);
        printf("label_%03d:\n", labelExit);
        PRNCMT("      ;; end if then\n");
    }
}
```

Quiz: Write the if-then-else case

# While Statement

---

```
void SyntaxWhileStmt::Translate(SymTable* symTable)
{
    ...
    int labelTest = newLabel();
    int labelExit = newLabel();

    printf("label_%03d:\n", labelTest);
    // result of test expr will be saved at rax
    test->Translate(symTable);
    printf("    cmp      rax, 0\n");
    printf("    jz       label_%03d\n", labelExit);

    // translate the body
    stmt->Translate(symTable);

    printf("    jmp      label_%03d\n", labelTest);
    printf("label_%03d:\n", labelExit);
}
```

# Function Call

---

```
void SyntaxFunctionCall::Translate(SymTable* symTable)
{
    int linkCount = 0;
    SymTableEntry* entry = symTable->Find(id, &linkCount);

    // push actual parameters
    if(params)
        params->Translate(symTable);

    // Call the function
    printf("    call    label_%03d ;  %s\n",
           entry->label, id);

    // Pop the parameters
    int actualParamSize = params?
                           params->TotalParamSize(): 0;
    printf("    add      rsp, %d\n", actualParamSize);
}
```

# Actual Parameters

---

\*In our implementation, SyntaxTree for formal and Actual Parameter lists are reversed

```
f(1, 2, 3) : 3 -> 2 -> 1

void SyntaxActualParamList::Translate(SymTable* symTable)
{
    if(next)
        next->Translate(symTable);
    expr->Translate(symTable);
    printf("    push    rax\n");
}

int SyntaxActualParamList::TotalParamSize()
{
    int exprSize = 8; // TODO: use the actual param size
    if(next)
        return exprSize + next->TotalParamSize();
    return exprSize;
}
```

Quiz: describe the stack for the actual parameters when `foo(1, 2, 3)` is called.

# Array Index

---

```
int Type::Size()
{
    FUNCTION_TRACE;

    switch(typeTag)
    {
        case TypeVoid:      return 0;
        case TypeInteger:   return 8;
        case TypeReal:      return 8;
        case TypePointer:   return 8;
        case TypeArray:     return arraySize * left->Size();
        case TypeProduct:   return (left? left->Size(): 0) +
                                (right? right->Size(): 0);
        case TypeFunction:  return 0;
        case TypeReference: return 8;
    }
    return 0;
}
```

Quiz: find the offset of `a[1][2][3]` from `a` when `a` is defined as  
`var a : array[10] of array[20] of array [30] of integer;`

# Array Index

---

```
void SyntaxArrayIndex::TranslateAsLValue(SymTable* symTable)
{
    int linkCount = 0;
    SymTableEntry* entry = symTable->Find(id, &linkCount);
    // Evaluate the indexes
    params->Translate(symTable);

    // Get the array size of each level from the type
    int arraySize[50], nas = 0;      // 50: up to 50 dimensional array
    for(Type *t = arrayType; t; t = t->left)
        arraySize[nas++] = t->Size();

    // Compute the index
    printf("    xor      rbx, rbx\n");
    while(--nas >= 1)
    {
        printf("    pop      rax\n");
        printf("    mov      rcx, %d\n", arraySize[nas]);
        printf("    imul     rcx\n");
        printf("    add      rbx, rax\n");
    }
}
```

# Array Index

---

```
// Add the index of id
if(entry->isGlobal)
    printf("    mov      rax, global_vars + %d ;  %s\n",
           entry->offset, entry->id);
else
{
    printf("    lea      rax, [rbp + %d] ;  %s\n",
           entry->offset, entry->id);
}

// Get the value of address if the entry is a reference
if(entry->type->typeTag == TypeReference)
    printf("    mov      rax, [rax]\n");

printf("    add      rax, rbx\n");
}
```

# Function Definition

---

```
void SyntaxFunctionDef::Pretranslate(
    SymTable* symTableBase)
{
    // For the new scope, create a new symbol table
    symTable = SymTable::PushNewTable(symTableBase);

    // Update the BASE symbol table for ID
    idEntry = symTableBase->Insert(id);
    int label = newLabel();
    idEntry->SetLabel(label);

    // Prepare this function's type.
    Type* type = new Type(TypeFunction,
        paramList->ToProductType(), returnType, 0);
    idEntry->SetType(type);
```

# Function Definition

---

```
...
// Update symbol table for formal params
// (actual params, return address, bp, local variables)
int offset = 8 + 8;      // 8 + 8: return address + push rbp
for(VarList *p = paramList; p; p = p->next)
{
    SymTableEntry* entry = symTable->Insert(p->id);
    Type *paramType = p->type;
    if(paramType->typeTag == TypeFunction ||
       paramType->typeTag == TypeArray ||
       paramType->typeTag == TypeProduct)
    {
        paramType = new Type(TypeReference, paramType, NULL, 0);
    }
    entry->SetType(paramType);
    entry->SetOffset(offset);
    offset += entry->size;
}

// Update symbol table for local variables
defList->Pretranslate(symTable);
}
```

# Function Definition

---

```
void SyntaxFunctionDef::Translate(SymTable* symTableBase)
{
    int offset = symTable->varSize;
    int label = idEntry->label;

    printf("label_%03d:\n", label);
    printf("    push    rbp\n");           // save and update rbp
    printf("    mov     rbp, rsp\n");
    printf("    sub     rsp, %d\n", offset); // space for local variables
    printf("    push    rbx\n");          // save registers
    printf("    push    rcx\n");
    printf("    push    rdx\n");
    printf("    push    r15\n");           // store for the return value

    bodyStmt->Translate(symTable);      // translate the body
    printf("    mov     rax, r15\n");       // copy the return value to rax

    printf("    pop    r15\n");           // restore registers
    printf("    pop    rdx\n");
    printf("    pop    rcx\n");
    printf("    pop    rbx\n");
    printf("    add    rsp, %d\n", offset); // reclaim the local var space
    printf("    pop    rbp\n");           // restore rbp
    printf("    ret\n\n");                // return to the caller
}
```

# Program Definition

---

```
void SyntaxProgramDef::Pretranslate(
    SymTable* symTableBase)
{
    // For the new scope, create a new symbol table
    symTable = SymTable::PushNewTable(symTableBase);

    // Update the symbol table with ID as a function
    idEntry = symTable->Insert(id);
    idEntry->SetType(new Type(TypeFunction, NULL,
        new Type(TypeVoid, NULL, NULL, 0), 0));
    int label = newLabel();
    idEntry->SetLabel(label);

    // Output the section before Pretranslate the defList
    printf("    global _start\n\n");
    printf("section .text\n\n");

    // Update symbol table for global variables
    defList->Pretranslate(symTable);
}
```

# Program Definition

---

```
void SyntaxProgramDef::Translate(SymTable* symTableBase)
{
    // global variable size
    int varSize = symTable->varSize;
    int label = idEntry->label;

    printf(" start:\n");
    printf("label_%03d:\n", label);

    bodyStmt->Translate(symTable);

    // exit(0)
    printf("    mov      eax, 60\n");
    printf("    xor      rdi, rdi\n");
    printf("    syscall\n\n");

    // Translate function/procedures
    defList->Translate(symTable);

    printf("section .bss\n\n");
    printf("global_vars:      resb      %d\n\n", varSize);
}
```

# Questions?

---